

USB2.0 Type-C PD240W Cable

No. WST-CUC001_2



Introduction

WST-CUC001 / WST-CUC002 are designed for high-performance charging, this USB-C cable supports an impressive 240W (48V/5A) Power Delivery, making it perfect for power-hungry laptops and workstations. It features gold-plated connectors for enhanced conductivity and 480Mbps data speeds with full backward compatibility. The combination of aluminum alloy housings and a reinforced soft PVC jacket ensures a sleek, robust, and bend-resistant build for long-lasting professional use.

Key Features

- USB2.0 Data transfer rates up to 480Mbps, backward compatible with USB1 .1.
- Supports Power Delivery up to 240W(48V/5A).
- Reversible USB-C connectors on both ends for effortless, orientation-free plugging.
- High-strength braided cable jacket enhances durability and tensile resistance.
- Encased in a reinforced soft PVC jacket for a sleek look, enhanced durability, and superior bend resistance.
- Featuring premium aluminum alloy housings for robust protection and long-lasting use.
- Equipped with gold-plated connectors and pins to enhance electrical conductivity and durability.

Package Contents

USB2.0 Type-C PD240W Cable x 1

Product Family

Item No.	Length
WST-CUC001	1M
WST-CUC002	2M

Specifications

Connector	
Connector A	USB Type-C Male
Connector B	USB Type-C Male
Connector Plating	Gold Plated
Pin Plating	Gold Plated
Housing	
Housing Material	Aluminum
Size W x D x H	11.4 x 7 x 32mm
Cable Construction	
Jacket Material	Soft PVC
Jacket Color	Black
Jacket Diameter	4.8mm
Conductor Gauge	30 / 30 / 23 AWG
Conductor Material	Tinned Copper
Shielding	
Housing Shielding	Tinplate
Technical Specifications	
Standard	USB 2.0
Supported Bandwidth	480Mbps
Minimum Bend Radius	48mm
Chipset	N/A
Country of Origin	China
Environment	
Operating Temperature	0° C~55° C
Storage Temperature	-10° C~60° C
Package	
Package Style	Polybag
Certification	
Safety & Emission	CE / FCC / RoHS / REACH